


We offer a range of laboratory equipment. Our facilities are ideally suitable for designing customer specific solutions. Some examples of our products are presented below.

OrderNb.	Name	Description	
1017.10.02	J1017-POWER	Constant current power supply specifically designed for use with stabilised light sources and calibration standard sources up to 220W (6.3A, 34V). Current resolution of 1mA. Manual front panel.	
105006	WLS100	The WLS100 is a general purpose fibre-coupled light source designed as a turn key solution for high power broad band output. The internal power supply guarantees an exceptional output stability. The optic ensures an efficient coupling into the fibre for maximum power output.	
602609	SHUNT-RESISTOR	The resistor has been developed for measuring of high DC currents. Manly used for measuring the current of calibration lamps up to about 10 A. DKD calibration certificate is available on request. Resistance: 100 mOhm Tolerance: 0,1% Temperature Coefficient: 1 ppm/°C	
100015	RSE-J1001	The optic RSR-J1001 is a special designed optic which allows on an easy and reliable way to measure the relative spectral response of a broadband radiometer. It fits exactly to the Bentham type spectroradiometer. Incl. adaptors for SL, YES, Kipp&Zonen, SCI.	
102203	UV-HG-J1022	Small ultraviolet calibration line source with 2 SMA light guide adaptors. Mercury-vapour discharge lamp. High output of ultraviolet radiation. Spectral emission consisting of many well-separated lines in the UV and VIS.	
1010xx	LI-J1010-xx-SMA-yy	Quartz glass light guides with SMA adaptor or individual designs. The light guides are assembled from single fibres to a bundle or as single fibres. Light guides are available with single or multi arms.	
101021 101047	-1a2m-SMA-bundle -1a8m-SMA-mono	Light guide; 1arm; 2 meter; fibre bundle Light guide; 1arm; 8 meter; one single fibre	
101002 101003 101056 101065	LI-J1010-FEEDTHROUGH LI-J1010-FEEDTHROUGH2 LI-J1010-FEEDTHROUGH3 LI-J1010-FEEDTHROUGH8	Feed through (light guides) with quartz fibre for UV-VIS are assembled by single fibre. The end is terminated with SMA connector/socket. M12x1 thread.	